



Fire Apparatus Quotation for: PEMBROKE PINES FIRE RESCUE



Quotation Number: 112611 Rev: 25

Unit Description: AERM-TYPN-100P

Quote Description: Aerial, Rear Mount, Aluminum, Typhoon, HP 100 Platform

Salesperson: RBELL

Salescode	Extended Description	Qty	
FRAME ASSEMBLY			
1250-0092	GEOMET coated frame assembly fasteners.	1	
1250-0098	Frame - Torque box for HP 100 platform (100KSI).	1	
AXLE OPTIONS			
1025-0023	Meritor RT-50-160 rear tandem axle 54,000 lb. capacity.	1	
1025-0028	Koni shock absorbers for front axle - adjustable.	1	
1025-0171	Dana D-2200W 24,000 lb. front axle. Includes maintenance free bushings. For use with disc brakes only.	1	
SUSPENSIONS			
1070-0015	Ridewell Dynalastic rear suspension (48-54K) rated equal to the capacity of the axles.	1	
TIRE OPTIONS			
1060-0008	Eight Michelin 12R tires model XZE for rear axles	1	
1060-0046	Two Michelin 425 tires model XFE for front axle.	1	
1060-0113	Intermittent service tire rating.	1	
1060-0200	PressurePro Pulse tire pressure monitoring system for tandem rear axle units. Includes recess mounted display in cab.	1	
BRAKE SYSTEMS			
1100-0007	Parking brake release mounted center of the engine cover.	1	
1100-0008	Brake system air 6X4/6X6.	1	
1100-0014	ArvinMeritor 16-1/2" x 7" S-cam brakes with cast brake drums for a tandem rear axle.	1	
1100-0020	Compression fittings for all air brake system lines. Includes cab interior air lines as applicable and accessories (if equipped).	1	

Salescode	Extended Description	Qty	
BRAKE SYSTEMS			
1100-0023	Stainless steel park brake release guard.	1	
1100-0026	G4 Electronic Stability Control (6x4), Includes RSC and ATC. Not available on 6x6 or commercial chassis.	1	
1100-0031	Dana ADB22X 17" disc brakes for front axle.	1	
INSPECTIONS AND PENALTIES			
1002-0001	Final inspection trip.	1	
1002-0002	Mid point inspection trip.	1	
TESTING COMPLIANCE STANDARD			
1001-0045	Unit to match as close as possible to previous unit. Documentation including photos, drawings and/or prints are available via shop order folder. Shop order information supersedes previous order. Similar to production order:	1	Manual added by DTALLMAN on 20-NOV-19
1001-0065	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition.	1	
3090-0003	OAH RESTRICTION. The unit has an overall height restriction and the height is not to be exceeded (unloaded condition).	1	12ft. 0in.
3090-0005	OAL RESTRICTION. The unit has an overall length restriction. The length is not to be exceeded.	1	47ft. 0in.
3090-0006	The hose bed is to have the capacity for the following hose. Hose load shall be listed from driver to officer.	1	Lay 1 - 350 ft. of 5.00 LDH Lay 2 - 300 ft. of 3.00 DJ Estimated Weight - 610 lbs.
3340-1137-12C	Equipment allowance on the apparatus shall be 2500 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1	
BUMPER TRAYS			
1150-0349	Bumper tray with floor/bottom slotted to allow drainage (no slats). Extending full width of the bumper as applicable based on outboard options. Includes notched frame extensions to provide as much depth directly above the extensions as possible based on options. Tray to have multiple depth to meet customer specific requirements.	1	Manual added by JNISWONGER on 06-SEP-18
1150-0456	Raised diamond plate lid with dual chrome grab handles, rubber hood latches and gas shocks. The lid shall be full width (as applicable based on outboard options) and high enough to accomodate reels, rescue tools and equipment as applicable per customer specific requirements. Front edge of lid to follow contour of bumper.	1	Manual added by JNISWONGER on 06-SEP-18
BUMPERS			

Salescode	Extended Description	Qty	
BUMPERS			
1160-0001	Bumper 12" high swept back stainless steel.	1	
1160-0008	3/16" Front Bumper Gravel Shield.	1	
1160-0015	24" Front Bumper Gravel Shield Extension.	1	
1160-0163	Rear bumper with 4" square steel tube for rear guard with No step tag. Marker lights to be attached to lower rear body surface. Bumper to be painted job color with Boston style corners cut at 30 degree angle on each end. (No rub rail or cover plate).	1	Manual added by JSTRAWDER on 28-JAN-19
WHEEL OPTIONS			
1050-0001	Alcoa aluminum wheels for front axle (2).	1	
1050-0005	Alcoa aluminum wheels for rear axles (8).	1	
1050-0007	Front axle wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. Note: Center cap will have an inspection port IPO a logo if equipped with Stemco oil seals.	1	
1050-0009	Rear axle (tandem) wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center caps with E-ONE logo. E-ONE custom chassis w/steel wheels will have chrome plated plastic lug covers.	1	
1050-0018	Each inside wheel of the tandem rear axles shall have valve stem extensions.	1	
AIR SYSTEM OPTIONS			
1110-0000-001	Inlet for air system. Location: driver door jamb.	1	
1110-0003	Air dryer System Saver 1200.	1	
1110-0004	Air tank drains w/pull cords.	1	
1110-0006	Air lines nylon.	1	
1110-0026	Air horns Hadley e-tone recessed in bumper (PR).	1	
1110-0027	Isolated air tank. Includes pressure protection valve.	1	
1110-0043	Auxiliary air tank to be plumbed to the following optional accessories (if equipped): Chassis air horns, brake system air outlet, air reel, light tower, air primer, air operated devices and or customer/dealer supplied pneumatic add-on(s).	1	
1110-0045	Gast air compressor 110v model 3HBB-32-M300AX.	1	
ENGINES & TRANSMISSIONS			
1200-0017	Push-button transmission shift selector.	1	
1200-0021	TranSynd, Shell Spirax S6ATF A295, or equivalent synthetic transmission fluid for EVS 4000.	1	

Salescode	Extended Description	Qty	
ENGINES & TRANSMISSIONS			
1200-0096	Electronic speed limiting set at 60 MPH. Note: Axle gear ratio will be as low as possible while allowing for 60 MPH top speed to improve acceleration.	1	
1200-0422	Eng/Trans Cummins X12 500HP with EVS4000 transmission. 2021 EPA Compliant.	1	
SECONDARY BRAKING			
1125-0002	Jacobs engine compression brake.	1	
1125-0023	Transmission to seek second gear when Jacobs engine brake or Telma retarder is engaged. N/A with Trans retarder.	1	
COOLING PACKAGE			
1800-0013	Cooling system for use with Typhoon, Cyclone and Quest chassis. For use with 2010 - 2021 EPA engines. Includes coolant recovery system.	1	
FUEL SYSTEMS			
1350-0005	Fuel system 65 gallons.	1	
1350-0022	Fuel line hose rubber.	1	
ALTERNATOR			
1700-0027	Alternator Leece Neville 420 amp. 420 amp SAE/369 amp NFPA.	1	
BATTERIES			
1400-0002	Battery four group 31 1000 CCA.	1	
CHASSIS OPTIONS			
1680-0005	Thermatic fan clutch.	1	
1680-0007	Drivelines 1810. Required on 1550 lb/ft torque or greater engines.	1	
1680-0008	Tow eyes front painted below bumper/cab (PR).	1	
1680-0012	Tow eyes rear frame painted black.	1	
1680-0017	Hot shift PTO.	1	
1680-0188	Aerial hydraulics installed on bottom port of EVS4000/4500 transmission (to allow for flat rear cab floor).	1	
1680-0250-M58	Diesel Exhaust Fluid (DEF) 5 gallon tank. Location: left side below rear of cab.	1	
1680-0284	Radiator mounted power steering cooler.	1	
CAB MODEL			
1520-0219	Typhoon medium cab with radial wipers (58" CA).	1	
CAB ROOF TYPE			

Salescode	Extended Description	Qty	
CAB ROOF TYPE			
1615-0023	Cab roof to have 12" high split raised rear section with full length center waterway trough. Inboard vertical surfaces tapered outward for use with HP100 Platform.	1	
CAB BADGE PACKAGE			
1610-0000	Cab and body to have applicable E-ONE logos.	1	
CAB DOOR OPTIONS			
1550-0003	Rear crew cab doors in the medium position.	1	
1550-0083	All cab exterior access doors to have CH751 keyed locks.	1	
1550-0159	Interior cab door locks - manual. Will be individually actuated from each respective door. Includes key lock on each exterior cab door handle.	1	
1550-0179-000-J7	Red/Fluorescent Yellow Green Reflexite V98 chevron "A" stripe on lower cab door panel approx 18" high. Stainless steel/painted door panels only. E-ONE cabs only.	1	
1550-0180	Cab door panels stainless steel. Includes upper and lower panels with seam below handrail.	1	
1550-0245	Anodized aluminum trim on the vertical edge of the over wheel cab compartment opening and/or rear cab compartment (ea).	1	
1550-0265	Anodize aluminum trim on bottom edge of the exterior cab compartment openings. Includes wheel well and rear compartments (as applicable).	1	
1550-0285	Driver and officer door windows to be power actuated with HD regulators. Switches to be located at center dash. For use with new Typhoon and 100" wide Cyclone cabs.	1	
1550-0286	Rear crew cab door windows to be power actuated with HD regulators. Switches to be located on each door with add'l switches accesible by driver. For use with new Typhoon and 100" wide Cyclone cabs.	1	
1550-0288	Cab doors to extend down to cover lower step well. For use with new Typhoon cab and 100" wide Cyclone only.	1	
CAB STEP OPTIONS			
1640-0047	Lower steps to extend 3.5" past cab. For use with legacy Typhoon / Cyclone with barrier style doors and 2019 Typhoon / 100" wide Cyclone with barrier style or extended doors.	1	
MIRRORS			
1670-0001-274	Ramco 6001FFR mirrors. Remote controlled with top CAS750 manual convex. Location: mounted on front corners of cab.	1	
1670-0031	2" extension for Ramco mirrors.	1	

Salescode	Extended Description	Qty	
MISC EXTERIOR CAB OPTIONS			
1550-0033	Windows cab side fixed officer's side.	1	
1550-0035	No window on the driver side of the cab	1	
1675-0022	Pair of 18" handrails located just behind driver and officer front door one each side.	1	
1675-0024	Pair of 36" handrails located just behind driver and officer rear door (ALS doors if equipped) one each side.	1	
1675-0030	Mud flaps, front, black with E-ONE logo.	1	
1675-0048	Rear cab wall to be smooth 3/16" aluminum plate with a diamond plate overlay.	1	Manual added by ARIOSECO on 04-FEB-19
1675-0201	Large radius cab wheel well. Includes bolt-on adjustable wheel well trim.	1	
1675-0202	Mounting plate for battery charger receptacle, indicator, air inlet, etc (if applicable). Plate to be removable brushed stainless steel.	1	
1675-0254	Rear cab and vista glass (if so equipped) to have dark tint IPOS. Glass to be smoked glass with 20% light transmittance (+/- 10%). Includes all glass rearward of front cab doors.	1	
HVAC			
1515-0053	Controls for heating and air conditioning shall be located in the center dash area. (Lower area on Typhoon and Cyclone with severe duty dash)	1	
1515-0102	Air conditioning with roof top mounted condenser. Includes reduced profile evaporator w/powder coated cover and electronic controls.	1	
1685-0057	Heaters cab rear with covers (PR), and front heater with heat to the feet for the driver and officer.	1	
SEATS			
1510-0004	Seats, Bostrom brand.	1	
1510-0007	Seat cover material vinyl.	1	
1510-0008	Seat color gray.	1	
1510-0057	Rear facing Bostrom seat with SCBA officer's side.	1	
1510-0063	Two man bench centered on rear wall with Bostrom SCBA. Includes angled corners.	1	
1510-0117-147	Bostrom SecureAll mechanical air pack bottle bracket (EA). Location: officer's seat.	1	
1510-0117-215	Bostrom SecureAll mechanical air pack bottle bracket (EA). Location: rear facing officer's side.	1	
1510-0131-151	Bostrom SecureAll mechanical air pack bottle bracket (EA) for bench / fold-down seat. Location: inboard driver's side rear wall.	1	

Salescode	Extended Description	Qty	
SEATS			
1510-0131-152	Bostrom SecureAll mechanical air pack bottle bracket (EA) for bench / fold-down seat. Location: inboard officer's side rear wall.	1	
1510-0533	Driver seat to be Bostrom air ride (Air-50 suspension) with Gen II design. Can be used with dual retractor upgrade (1510-0508).	1	
1510-0535	Officer seat to be Bostrom air ride SCBA with Gen II styling. Includes slide tracks for front to rear seat adjustment. Can be used with dual retractor upgrade (1510-0508).	1	
1685-0032	Seating capacity tag of five occupants.	1	
MEDICAL CABINETS			
1535-0168	All cab exterior ALS/medical cabinet doors to have 1250 keyed locks.	1	Manual added by WYOUNG on 26-SEP-19
1535-0202	Cab medical/storage cabinet(s) finish to be Zolatone gray. Includes interior/exterior of cabinet and shelves/trays if equipped.	1	
1535-0208	Driver side cab wheel well medical cabinet with external locking pan door painted job color. Cabinet includes (2) adjustable shelves. Cabinet is approximately 42H x 22W x 28D on Typhoon and Cyclone and 42H x 25W x 28D on 100" wide Cyclone and Quest (viewed from interior).	1	Manual added by WYOUNG on 27-FEB-19
MISC INTERIOR CAB OPTIONS			
1685-0005	Lexan sun visors, driver and officer's side overhead.	1	
1685-0008	Control lanyard Y type for air horns.	1	
1685-0119	3/16" Aluminum plate on top engine cover forward of access door. To have swirl finish and be spaced up approx 1/2".	1	Manual added by WYOUNG on 27-FEB-19
1685-0187	Severe duty engine cover, molded polyurethane.	1	
1685-0221	Severe duty dash package. Includes smooth plate alum center and officer side dash painted to match cab interior and lower dia plt kick panels. Officer cab dash notched with recessed glove box. Includes angled notepad holder on top.	1	Manual added by WYOUNG on 07-SEP-18
1685-0261	Storage below rear bench seat. (1) cargo net (black) on each side of the bench seat to gain access to storage area.	1	Manual added by WYOUNG on 20-MAY-19
1685-0440	Storage below rear bench seat. Cargo netting cover on the front of the rear bench seat.	1	Manual added by WYOUNG on 20-MAY-19
1685-0446	Severe duty overhead console. Includes driver, center and officer overhead ahead of air conditioning plenum. Center overhead includes siren mounting locations. Overhead to match cab interior.	1	
1685-0531	Reduced profile rear engine cover for increased legroom.	1	
1685-0692	Cab insulation package. Includes insulation for ceiling, front wall, rear wall, side walls, below seat risers and in doors.	1	

Salescode	Extended Description	Qty	
MISC INTERIOR CAB OPTIONS			
1685-0891	Cab interior padding to be gray.	1	
CAB ELECTRICAL OPTIONS			
1750-0016	Pump hourmeter in cab.	1	
1750-0021	Battery charger Kussmaul model 1200, 40 amp.	1	
1750-0024-179-04	Auto-Eject receptacle inlet 20 amp located outside driver's door next to handrail with a Yellow cover.	1	
1750-0029	Switch horn button two position DOT/air horn.	1	
1750-0046-195	Cab Headlights. Position: lower.	1	
1750-0072-545	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: In cab driver side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
1750-0072-592	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: driver side dash.	1	
1750-0072-593	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: officer side dash.	1	
1750-0072-596	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: map box.	1	Manual added by JNISWONGER on 06-SEP-18
1750-0072-748	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: officer side rear cab wall in or below seat support structure as space allows.	1	
1750-0072-964	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: forward wall of driver side medical/ALS cabinet(s).	1	Manual added by JNISWONGER on 26-SEP-19
1750-0075	English dominant main cab gauge cluster.	1	
1750-0158	Dome Lts Weldon Red/White LED. Package includes two lights mounted in the front and two mounted in the rear of the cab. White light wired through door and light assembly switch. Red light through light assembly switch.	1	
1750-0198-762	Battery charger to be located behind officer's seat.	1	
1750-0199-A31	Air compressor to be located behind driver's seat.	1	Manual added by JNISWONGER on 26-SEP-19
1750-0215-172	Turn signal Whelen M6 LED arrow amber pair located upper headlight bezel.	1	
1750-0429-545	Dual USB charging ports wired battery hot. Location: In cab driver side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
1750-0429-592	Dual USB charging ports wired battery hot. Location: driver side dash.	1	
1750-0429-593	Dual USB charging ports wired battery hot. Location: officer side dash.	1	
1750-0429-747	Dual USB charging ports wired battery hot. Location: driver side rear cab wall in or below seat support structure as space allows.	1	
1750-0429-748	Dual USB charging ports wired battery hot. Location: officer side rear cab wall in or below seat support structure as space allows.	1	
1750-0429-Q22	Dual USB charging ports wired battery hot. Location: driver side interior backwall of map box.	1	Manual added by JNISWONGER on 06-SEP-18

Salescode	Extended Description	Qty	
CAB ELECTRICAL OPTIONS			
1750-0449	Momentary DPF regeneration override switch.	1	
1750-0554	FireTech LED cab headlights.	1	
1750-0582	Light EON LED (EA) mounted in bench seat riser. The light(s) shall be wired through the compartment door switch(s) or rocker switch as applicable if equipped with cargo nets.	1	
1750-0764	Daytime Running Light TecNiq LED strip (PR) with polished alum housing located between quad headlight bezels (New Typhoon and 100" wide Cyclone only).	1	
1750-0768	TecNiq D07 LED cab door step area lighting. Includes (2) lights at each door area. Lights to be switched with door ajar.	1	
BODY SPEC			
3090-0000	Body Specs - SideStacker aerial with tandem axle. Includes left rear staircase with pocket style drop down step.	1	
BODY COMPT REAR			
3110-0360	Rear of body to have un-painted smooth plate overlay style body panels to facilitate rear body striping.	1	
AERIAL BODY OPTIONS			
3310-0032	Recessed tubes for (6) pike poles. Not available on HP75 SideStacker.	1	
3310-0069	Rear ladder tunnel doors. Vertically hinged smooth plate to match rear body finish.	1	
3310-0072	Compartments driver side HP100 Platform SideStacker with 300g tank. Includes rescue style extended height compartments. The door on small compts next to rear outrigger to match wheelwell.	1	
3310-0074	Compartments officer side HP100 Platform SideStacker with 300g tank. Includes rescue style extended height compartments ahead of wheel well, compartment over forward tandem and extended hosebed.	1	
3310-0075	Upper dunnage area extension 34 x 58 diamond plate.	1	
3310-0076	Body wheelwell compartments (4) approx 24" W x 6" H x maximum depth permissible without interference with hydraulic line(s) reservoir(s) etc. A gasketed drop down door shall be installed on each compartment. Door material to match wheelwell finish.	1	
3310-0096	Doors for rear master and jack control controls. Doors will match rear body finish.	1	
3310-0162	Jack leg opening covers diamond plate (4) sets. Includes diamond plate outrigger covers and fixed diamond plate filler panels. HM100/110 requires surface mount warning lights.	1	

Salescode	Extended Description	Qty	
AERIAL BODY OPTIONS			
3310-0310	Auxiliary jack pad 26X26 (4) with 20 degree formed handle. Includes (2) double mounting brackets.	1	
3310-0769	Crosslay double w/dry lay. Includes (2) 5.5" wide single stack crosslays to hold up to 200' of 1.75" DJ or 150'-200' 2.0" DJ (each) and (1) dry lay for up to 300' of 3.0" DJ to be deployed from Officer side ONLY.	1	Manual added by JSTRAWDER on 27-SEP-19
DOORS			
3300-0007-018	Door single vertical hinged painted. Location(s): R4	1	
3300-0007-019	Door single vertical hinged painted. Location(s): R5	1	
3300-0007-020	Door single vertical hinged painted. Location(s): R6	1	
3300-0011-005	Door single horizontal hinged lift-up box pan configuration painted. Location(s): L3	1	
3300-0011-006	Door single horizontal hinged lift-up box pan configuration painted. Location(s): L4	1	
3300-0011-017	Door single horizontal hinged lift-up box pan configuration painted. Location(s): R3	1	
3300-0017-007	Door roll up short (up to 45") with satin finish ROM. Location(s): L5.	1	
3300-0019-003	Door roll up tall (greater than 45") with satin finish ROM. Location(s): L1.	1	
3300-0019-004	Door roll up tall (greater than 45") with satin finish ROM. Location(s): L2.	1	
3300-0019-015	Door roll up tall (greater than 45") with satin finish ROM. Location(s): R1.	1	
3300-0019-016	Door roll up tall (greater than 45") with satin finish ROM. Location(s): R2.	1	
3300-0062-005	Keyed compartment door latch with #1250 key. Location(s): L3.	1	
3300-0062-006	Keyed compartment door latch with #1250 key. Location(s): L4.	1	
3300-0062-017	Keyed compartment door latch with #1250 key. Location(s): R3.	1	
3300-0062-018	Keyed compartment door latch with #1250 key. Location(s): R4.	1	
3300-0062-019	Keyed compartment door latch with #1250 key. Location(s): R5.	1	
3300-0062-020	Keyed compartment door latch with #1250 key. Location(s): R6.	1	Manual added by JSTRAWDER on 12-NOV-19
3300-0063-003	Keyed roll-up compartment door with #1250 key. Location(s): L1.	1	
3300-0063-004	Keyed roll-up compartment door with #1250 key. Location(s): L2.	1	
3300-0063-007	Keyed roll-up compartment door with #1250 key. Location(s): L5.	1	
3300-0063-015	Keyed roll-up compartment door with #1250 key. Location(s): R1.	1	
3300-0063-016	Keyed roll-up compartment door with #1250 key. Location(s): R2.	1	
3300-0066-003	Drip pan for a ROM roll-up door (EA). Location(s): L1.	1	

Salescode	Extended Description	Qty	
DOORS			
3300-0066-004	Drip pan for a ROM roll-up door (EA). Location(s): L2.	1	
3300-0066-007	Drip pan for a ROM roll-up door (EA). Location(s): L5.	1	
3300-0066-015	Drip pan for a ROM roll-up door (EA). Location(s): R1.	1	
3300-0066-016	Drip pan for a ROM roll-up door (EA). Location(s): R2.	1	
3300-0368	Pull-down bungee type straps for full height and high side roll-up door(s) on body / pump module. For use with ROM and AMDOR doors only.	1	
SHELVES			
3370-0245	Permanent fixed shelf. Aluminum or stainless steel body applications. Location:	4	L1; L2; R1; R2
3370-0246	Adjustable shelf for non-transverse compartments. Location:	5	L2; L5; R2; R4; R6
3370-0247	Tracks for adjustable shelf and/or adjustable tray in a compartment. Location:	5	L2; L5; R2; R4; R6
TRAYS / TOOLBOARDS			
3380-0019-136	Running board suction tray. Includes removable slats in bottom of tray. Location(s): officer side running board	1	
3380-0498	Tray, floor mounted roll-out with gas spring. 500 lbs. capacity. Location:	4	L2; L5; R2; R6
COVERS			
3305-0001	Hosebed cover aluminum (2) piece with recessed handles, SideStacker. Note: This option effects hose bed capacity.	1	
3305-0003	Single diamond plate cover for the crosslay area. Includes applicable grab handle(s) and (2) butterfly style latches.	1	
3305-0004	Crosslay cover to be hinged forward.	1	
3305-0022-000-02	Vinyl rear cover for diamond plate hose bed cover. Color: Red.	1	
3305-0024-000-02	Vinyl Red side covers for diamond plate crosslay cover.	1	
3305-0064-136	Nylon black strap with stainless steel quick-release buckle for hose tray. Strap to attach to side walls of tray down low as applicable. Location: officer side running board.	1	
3305-0119	Hold open device(s) for aluminum crosslay (single or bi-fold) cover. Locate as required based off options on module.	1	
PUMP PANELS			
3134-0016	Stainless steel driver and officer side pump panels.	1	
3134-0143	Officer side pump panel to be vertical hinged on forward extrusion. Panel to be (3) pieces with upper (2) panels secured in the closed position with push button latches. Upper panel to be held open with gas shock.	1	
3134-0208	Driver side pump panel to have a removable Escutcheon plate needs to be as	1	Manual added by JSCIANNI on 24-SEP-19

Salescode	Extended Description	Qty	
PUMP PANELS			
	large as possible. Customer would like it to be hinged to the front .		
MISC PUMP PANEL OPTIONS			
4460-0003	Pump panel tags color coded per NFPA compliance.	1	
4460-0009	Pump panel tags, special color. (Must specify.)	1	Match Color and Verbiage on 142960
4460-0010	Pump panel tags - Special label. (Must specify.)	1	Match Color and Verbiage on 142960
4460-0012	Panel support. Vertically hinged panels to have support bracing provided along internal side of main panel only.	1	Manual added by JSCIANNI on 14-DEC-18
4460-0088-282	Air outlet with Innovative Control 1/4" valve w/1/4 turn "T" handle and label for: driver's side pump panel.	1	
4460-0088-283	Air outlet with Innovative Control 1/4" valve w/1/4 turn "T" handle and label for: officer's side pump panel.	1	
PUMP MODULE OPTIONS			
3136-0029-202	Air horn switch at pump panel. Switch to be labeled "Air Horn". Location: driver side pump panel.	1	Manual added by JSTRAWDER on 27-SEP-19
WATER TANK			
4010-0195	300 gallon "T" water tank. UPF Poly III blue fill tower.	1	
TANK PLUMBING			
4450-0010	2" tank fill Akron manual valve.	1	
4450-0022	3" tank to pump Akron manual valve.	1	
LADDER STORAGE / RACKS			
3365-0076-Q04	Center mounted ladder tunnel for HP100 and HPS100 Platforms. Note: 1" aerial raise required with 30' and larger 3-section ladder in tunnel. Rack to hold: (2)PEL-35, PEL-28, PEL-24, PRL-20, PRL-16 and FL-10 (with rubber block feet and no handles).	1	
HANDRAILS / STEPS			
3330-0002-050	Slide-out platform, rollerless. Includes chrome grab handle centered on the front face of the platform (includes hand rail as applicable). Located below driver side pump panel.	1	
MISC BODY OPTIONS			
3340-0035	Divider Long. To run full length of hose bed (front to rear).	1	Manual added by JSTRAWDER on 12-NOV-19
3340-0058	Recessed fuel fill driver side wheel well.	1	
3340-0090-000-13	Turtle Tile Brand Black Floor Matting covering all applicable Compartment Floors,	1	

Salescode	Extended Description	Qty	
MISC BODY OPTIONS			
	Shelves, and Rollout Trays. Does not include roof top compartments (Added separately)		
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0270	The painted aerial body side panels shall be smooth / flush. Applies to SideStacker HB side, panels next to water tank on MM, and upper body sides on RLP or RLX.	1	
3340-0405	Sign, "STAY BACK 500 FEET" with black reflective lettering. Locate below rear of body.	1	
3340-0653	Diamond plate tandem axle wheel well. Includes bolt-on composite wheel well liners and bolt-on polished alum fenderettes.	1	
3340-1632	Diamond plate corner guard for the rear compartment face forward of staircase(s). Guard to wrap around the corner. SideStacker or NPNT w/ side staircase aerial bodies only.	1	
3340-1648	Anodized aluminum trim on bottom edge of all body compartment openings including pump enclosure if applicable with painted edges.	1	
SCBA BOTTLE STORAGE			
3320-0018	SCBA Bottle Storage. (8) Fire Shopp SCBA bottle storage with hinged doors with push button latches. (4) officer side and (4) driver side in wheel well area.	1	
3320-0100	Strap, loop style to retain SCBA bottle(s). Locate one per bottle in each exterior body storage compartment.	1	
PUMPS			
4005-0032	Rating 1750 GPM	1	
4005-0196	Hale QMAX 1000-2250 GPM single stage pump. Requires primer option.	1	
PUMP CERTIFICATION			
4475-0000	Pump certification 750-2250 GPM	1	
PUMP OPTIONS			
4015-0008	Zinc anodes for Hale pump (PR), (1) discharge side and (1) intake side.	1	
4015-0012	Pump shift override, side panel mounted.	1	
4015-0022	Mechanical pump seal - Hale.	1	
4015-0029	Hale pressure relief valve. Hale Qmax, or Qflo only.	1	
4015-0037	Engine throttle, vernier.	1	
4015-0045	Throttle Selection Switch on Pump Operator's Panel for Back-Up of Relief and Throttle System.	1	

Salescode	Extended Description	Qty	
PUMP OPTIONS			
4015-0052-198	Steamers to be Flush. Location: driver's side.	1	
4015-0052-199	Steamers to be Flush. Location: officer's side.	1	
4015-0073	Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location below running board on driver side (or area directly to rear of panel if no room below panel).	1	
4015-0210	Pump cooler with Innovative Control 1/4 turn valve with "T" handle and label.	1	
4015-0242	Trident primer W/3 barrel push button control. For use with 1250 GPM and larger pumps. Requires 15.6 CFM or larger engine air compressor.	1	
INTAKES			
4440-0005	2.5" Left Intake Akron Manual Valve.	1	
4440-0006	2.5" Right intake Akron manual valve.	1	
INTAKE OPTIONS			
4445-0048	Intake pressure relief valve, Task Force Tips.	1	
DISCHARGES AND PRECONNECTS			
4415-0008	1.5" Front bumper discharge Akron manual valve.	1	
4415-0012-654	1.5" Crosslay with Akron manual valve. Location: crosslay 1 & 2.	2	
4415-0014-581	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1.	1	
4415-0014-582	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 2.	1	
4415-0016-584	2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 2.	1	Manual added by JSCIANNI on 16-MAY-19
4415-0176-210	Brass Swivel in Tray center front bumper for Front Bumper Discharge.	1	
4415-0429-583	3" Right Pump Panel Discharge Akron Valve Handwheel Control (Waterous pumps noted location to be forward lower port). Location: right side discharge 1.	1	Manual added by JSCIANNI on 16-MAY-19
4415-1274	4" waterway discharge w/ Akron electric valve. Requires valve controller option.	1	
DISCHARGE OPTIONS			
4417-0175	Innovative Controls push/pull valve controls with locking T handles.	1	
4417-0176	Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip.	8	Manual qty change by JSCIANNI on 16-MAY-19
4417-0185	Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel.	1	

Salescode	Extended Description	Qty	
DISCHARGE OPTIONS			
4417-0313-359	Akron 9333 Navigator Pro 2 electric valve controller with full color LCD display. Locate on pump operator panel to control waterway discharge.	1	
PRESSURE GOVERNORS			
4465-0011	Class 1 TPG pressure governor. Includes, water, oil, volt and tachometer.	1	
GAUGES			
4435-0026-359	Flowminder System. Discharge: waterway discharge.	1	
4435-0030	Transmission temperature gauge on pump operator's panel.	1	
4435-0031	Pump hourmeter on pump operator's panel.	1	
4435-0034	Fuel level gauge on pump operator's panel.	1	
4435-0069	Class 1 ENFO IV system on pump operator's panel.	1	
4435-0083	Innovative Controls 10 LED SL series water tank level gauge. On pump panel.	1	
4435-0246	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel.	8	Manual qty change by JSCIANNI on 16-MAY-19
4435-0247	4" Innovative Controls stainless steel case master pressure gauges with bezel. Intake 30-0-400, and discharge 0-400.	1	
4435-0273	Class 1 flow meter totalizer button. Location Pump operator panel.	1	
4435-0418	Pump overheat indicator - Innovative Controls. Includes alarm.	1	
ELECTRICAL SYSTEMS			
5010-0013-171	Vehicle data recorder - 2009 / 2016 NFPA compliant. Includes occupant detection with display. Display location: driver's overhead.	1	
5010-0039	V-MUX Electrical system for aerals.	1	
5010-0094	Nanoprotech corrosion inhibiting spray coating to be applied on all exposed electrical connections.	1	
5010-0100	AXIS Smart Truck Technology. Includes roof mounted antenna and 5 year data plan. For use only with E-ONE chassis in the USA.	1	
5010-0121-171	LCD Info Center (text display) for V-MUX electrical system. Location: driver's overhead.	1	
LIGHT BARS			
5300-0506-000-4V	Front light bar LED color: Red/White with clear lenses (If applicable, includes side facing when colors are the same.)	1	
5300-0514	Whelen MK9S short slide bolt bracket mount for mini front light bars (4).	1	Manual added by JNAWROCKI on 20-DEC-18
5300-0523	Whelen F4 Mini-Freedom LED side facing front cab light bars (PR) 21.5" . For use on rear mount platforms with supplemental upper level Zone A warning lights.	1	

Salescode	Extended Description	Qty	
LIGHT BARS			
	Locate one each side front cab corners side facing.		
WARNING LIGHT PACKAGES			
5550-0225-535	Whelen M6 Super LED lower level warning light package. Includes (8) red M6RC LED light heads with clear lens and (2) red M2RC LED light heads with clear lens. Locate side facing lights: at forward most position, centered in rear wheel well, and side facing at rear of body in rubrail if equipped.	1	
WARNING LIGHTS			
5600-0078-290-R4	Whelen Super LED beacon (PR) model L31H with Red LED with Clear lens domes. Location above L2/R2 compartments offset rearward to supplement upper rear warnings.	1	
5600-0105-170	Hazard (door ajar) light 2" LED. Location: center overhead.	1	
5600-0139-479-06	Whelen beacon with LED upper beacon and 700 series Super LED (PR) model B6LED with red LEDs/clear domes and Red LEDs/clear lenses. Location: rear upper body on aerial style brackets.	1	
5600-0286-464	Warning light Whelen M6RC series Super LED (PR) red with clear lens. Location: (1) each side of cab down low just ahead of rear doors.	1	
DIRECTIONAL LIGHT BARS			
5310-0020-846	Directional light bar control is to be located center overhead console offset to driver side.	1	
5310-0028	Whelen Traffic Advisor Model TAM83 LED - 31" long, with clear lenses.	1	
SIRENS			
5500-0009	Federal PA300 electronic siren recessed mounted.	1	
5500-0011-209	Federal Q2B siren - Pedestal mounted on bumper. Location: driver side front bumper. Requires activation switch.	1	
5500-0024-847	The primary electronic siren control is to be located center overhead console offset to officer side.	1	
SPEAKERS			
5510-0029-209	Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: driver side front bumper.	1	
5510-0029-211	Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: officer side front bumper.	1	
DOT LIGHTING			
5150-0017	License plate light LED with chrome housing located at the rear of the body.	1	

Salescode	Extended Description	Qty	
DOT LIGHTING			
5150-0028	Marker light Truck-Lite LED body/cab package. E-ONE custom cab with rear mount aerial platform bodies only. Includes (3) marker lights on front of platform.	1	
5150-0032	Bracket license plate at rear of body. Tread plate bracket.	1	
5150-0039	Marker lights Britax amber/red rubber housed mounted on the rear body corners angled down.	1	
5150-0102	Whelen M6 series LED vertical mount tail lights. Includes LED stop/tail, arrow turn and back-up lights with vertical 3 light housing and weatherproof connectors.	1	
LIGHTS - COMPARTMENT, STEP & GROUND			
5380-0247	Compartment light ROM V4 LED for medical cabinet (EA).	1	
5380-0254	Compartment light package ROM V4 LED for large bodies. Includes two lights per compartment (four if transverse).	1	
5380-0280	Ground light package TecNiq T440 4" LED - large.	1	
5380-0285	Step light package body TecNiq T440 4" LED - small.	1	
5380-0323	The auxiliary steps below the cab doors and/or below pump module/body (if applicable) to have EON LED lights to illuminate the stepping surface and ground below (IPO lights indicated in the main ground light package).	1	
5380-0325	EON LED ladder tunnel light (EA).	2	
LIGHTS - DECK AND SCENE			
5390-0087-446	Whelen M6 Linear Super LED scene lights (PR). Switched in cab (lights mtd on the sides of apparatus to be switched separately). Locate (1) each side at rear below pike pole compts.	1	
5390-0088	Crosslay light Whelen PFBP12C LED. Locate to rear of crosslay (SM) and forward of crosslay (TM as applicable). Switched with work light switch in cab.	1	
5390-0230	Hose bed light FireTech model WL2000 LED with white housing. Locate center front of hose bed. Switched with work light switch in cab.	1	
LIGHTS - NON-WARNING			
5400-0043-166	Maplight-Little Lt 18" Flex at officer's A post. Includes on/off switch.	1	
5400-0150	Pump panel LED light package for side mount. Includes (6) Tecniq EON lights with S/S housings located (3) ea side. Includes S/S light shields (as applicable with intermedialte steps).	1	
5400-0185	LED pump compartment light (EA).	1	
5400-0224	Engine compartment light Optronics LED Series ILL22 (EA).	1	

Salescode	Extended Description	Qty	
LIGHTS - NON-WARNING			
5400-0242-270	TecNiq LED backing lights (PR) model E60-WS20-1flush mount docking/backing light. Location: rear wheel well offset to rear.	1	
CONTROLS / SWITCHES			
1750-0034-A24	Switch, additional 12 volt/15 amp. Location and function: driver rear of body for rear work lights.	1	
5100-0001-16Q	Switch circuit three way. Includes (1) additional switch. An additional switch required for more than two locations. Location: accessible to driver for 12V flood light on front of platform.	1	Manual added by JNISWONGER on 25-FEB-19
5100-0006-198	Foot switch to control Q2B located driver's side.	1	
CAMERAS / INTERCOM			
5350-0001	Camera back-up Safety Vision LCD model SV-CLCD70BA-625B with audio. For use with up to 2 cameras.	1	
5350-0103-X09	The back-up camera monitor is to be located on the center dash offset driver.	1	
5350-0107-H72	Intercom base unit to be located below officer's seat.	1	Manual added by JNISWONGER on 26-SEP-19
5350-0182	Safety Vision officer's side camera SV-622RS w/ SV-512 cable. Requires Safety Vision back-up camera option. Camera to be located on front cab corner (approx 31" bottom of camera to bottom of cab) interlocked with right turn signal. Camera only - does not include monitor.	1	
5350-0244-202	FRC ACT 3-way aerial intercom to provide communications between the turntable control station, the aerial tip and driver side pump panel.	1	
5350-0319	FireCom wireless intercom kit to include a digital intercom model 5100D, one (1) base transmit unit with up to (5) radio/intercom only transmission and up to (5) headset hooks shall be installed within the cab. Headsets are not included and ordered separately (misc loose equip).	1	
5350-0419	Rosco dual vision HD camera system model DV440. Interior mounted at the front windshield.	1	Manual added by JNISWONGER on 05-SEP-19
MISC ELECTRICAL			
5110-0017	Back-up alarm 97 dB.	1	
5110-0219-762	Blue Sea 12V power distribution module model 5032. Location: behind officer's seat.	1	
LIGHTS - AREA			
5450-0313-437	FireTech 11" 12V double stack brow light powder coated white with flood optics. Includes switch in cab (driver and officer side facing lights switched separately). Location: driver and officer side front cab brow	2	Manual added by JNISWONGER on 25-FEB-19

Salescode	Extended Description	Qty	
LIGHTS - AREA			
5450-0337-493	FireTech 35" 12V mini brow light with white housing and flood optics. Includes switch in cab (driver and officer side facing lights switched separately). Location: driver and officer side over rear cab door.	2	
RECEPTACLES			
5470-0004-964	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: forward wall of driver side medical/ALS cabinet(s).	1	Manual added by JNISWONGER on 26-SEP-19
AERIAL MODEL			
6100-0117	Platform HP100 with -10 degree travel and fabricated SideStacker style turntable. Includes left side console, turntable mansaver bars and jack leg flood lights.	1	
AERIAL HYDRAULIC SYSTEM OPTIONS			
6150-0003-216	Gauge aerial hydraulic oil level. Electronic display to be located on pump operator's panel.	1	
AERIAL CONTROLS			
6850-0012	Hinged cover for platform control console. Swirl finish smooth plate with gas spring hold-open.	1	
6850-0037	Advanced Aerial Control System - Platform. Includes body protection, cradle alignment It and 3.2" displays with flowmeter at each control console.	1	
6850-0043	Diamond plate turntable console mounted to tube style pedestal mount. Includes side hinged diamond plate cover with hinge on outboard side. Includes modified left side turntable handrail. (95-platform and HP/HPS100 Platform only)	1	
6850-0054	Handheld tethered control in platform for aerial movement. Includes storage area recessed in console.	1	
6850-0056	Deadman foot switch for aerial controls located at turntable console. For use with AACS only.	1	
6850-0057	Deadman foot switch for aerial controls located in platform below console. For use with AACS only (std with Deluxe systems).	1	
6850-0081	Platform leveling system with assist to allow adjustment of platform pivot angle from cab. Includes two switches, one with multi-color light accessible by driver to indicate platform is in alignment with ladder and a second switch for platform level assist.	1	
MONITORS			
6300-0018	Monitor painted job color. (Akron and Elkhart Scorpion only).	1	
6300-0115	Monitor Elkhart Scorpion EXM electric with SM-2000E nozzle for platform. Includes tip controls, base controls and a butterfly valve. (Note: Requires	1	

Salescode	Extended Description	Qty	
MONITORS			
	seperate interface control module if unit does not have AACs)		
AERIAL WARNING LIGHTS			
6550-0002	Outrigger warning lights (4) LED. Truck-Lite model 91R.	1	
6550-0033-224-4T	Whelen M6 Super LED Red with clear lenses warning lights on platform (PR). The lights shall be switched with aerial master and located on each side on on the side of the ground pad brackets.	1	
6550-0049	Whelen M6 series Super LED red warning lights with clear lenses model number M6RC (4). Located down low across front of platform wired to upper level lights.	1	Manual added by JNISWONGER on 26-SEP-19
AERIAL LIGHTING			
6560-0084-000-03	Ladder climbing lights Luma-Bar Pathfinder LED strip for 95-Platform and HP100 Platform (one side). Color: Blue.	1	
6560-0127	FireTech model FT-WL3500-FT-W LED flood/spot light with white housing. Includes hardwired switch on turntable console. Location: left and right side of base section.	1	
6560-0247-237	Light Whelen Pioneer Plus flood 12V model PFH1with bail mount platform mounted powder coated white. Includes hardwired switch on platform console. Location(s): center front of platform.	1	
6560-0247-3TX	Light Whelen Pioneer Plus flood 12V model PFH1with bail mount platform mounted powder coated white. Includes hardwired switch on platform console. Location(s): right side, rear bottom (underneath) of the platform, pointed approx 30 degrees down and forward.	1	Manual added by JNISWONGER on 25-JAN-19
6560-0247-3TY	Light Whelen Pioneer Plus flood 12V model PFH1with bail mount platform mounted powder coated white. Includes hardwired switch on platform console. Location(s): left side, rear bottom (underneath) of the platform, pointed approx 30 degrees down and forward.	1	Manual added by JNISWONGER on 25-JAN-19
6560-0261-241	Whelen Pioneer PFH2 12V LED floodlight with pole mounted at platform. Includes switch on light head. The light shall be located right rear of platform.	1	Manual added by JNISWONGER on 25-JAN-19
6560-0299-31G	FireTech 14" 12V mini single stack trunnion mount light powder coated white. Includes switch on platform console. Location: right front corner of platform.	1	Manual added by JNISWONGER on 26-SEP-19
6560-0299-P21	FireTech 14" 12V mini single stack trunnion mount light powder coated white. Includes switch on platform console. Location: left front corner of platform.	1	Manual added by JNISWONGER on 26-SEP-19
WATERWAY OPTIONS			
6350-0002-192	Elkhart 2.5" valve for platform. Valve to be located at the front of platform next to monitor.	1	
6350-0005	Rear 4" NST waterway inlet for rear mounted aerals. Includes chrome cap.	1	
6350-0014	2.5" chrome elbow with 2.5" x 1.5" reducer and 1.5" cap for platform / ladder	1	

Salescode	Extended Description	Qty	
WATERWAY OPTIONS			
	discharge valve.		
6350-0067	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel. Locate next to waterway inlet.	1	
BREATHING AIR			
6400-0003	Breathing air platform with (1) 444CF cylinder. Includes low air alarm.	1	
6400-0010	Additional breathing air outlet at turntable console. Includes filter.	1	
6400-0011	Breathing air outlets additional in platform (PR).	1	
6400-0020	Fill hose for aerial breathing air system 50' 7000 PSI.	1	
AERIAL EQUIPMENT			
6500-0000-221	Hose box for 50' of 1.75" DJ hose located left side of platform.	1	
6500-0019-266	Axe bracket mounted on aerial. For use with a 6 lb. axe only. Location: right side inside of platform.	1	
6500-0023	Dual rope roller for aerial.	1	
6500-0027	Lifting eye / tie-off package for HP/HPS100 Platform. Includes lifting eyes each side (below mainrail) at tip of base and a tie-off point on each turntable trunnion.	1	
6500-0028	Rappelling rope guides located each side on front hand rail of platform. 95-Platform with taper corner bucket, HP95MM and HP/HPS100 Platforms only.	1	
6500-0086	Stokes basket diamond plate storage box for Ferno Washington model 71 or Ferno Washington Advantage model RE1125 stokes on aerial base section. Includes hinged lid with gas springs & notch to clear extension system components. Locate right side on side of base section ahead of sign plate (if equipped). HP100 platform only	1	Manual added by JSTRAWDER on 26-SEP-19
6500-0105	PAC TRAC postive locking bracket (PR) for 8' pike pole on ladder includes stop plate to prevent the pole from sliding. location: left side of base horizontally mounted behind sign plate.	1	
6500-0151	Stokes basket receiver for HP/HPS100 Platforms. Stokes and storage brackets on side of base not included.	1	
AERIAL LADDER BRACKETS			
6600-0002-250	Roof ladder bracket J style mount. Locate outside base section for a PRL-16 on left side of base section. Available on HP75/78, HP100, and HP95. Requires engineering review and approval on HP75 with split raised roof.	1	
6600-0009	Parapet roof ladder bracket for platform. For use with Alcolite and Duo Safety roof ladders (not included). Available on HP100 Platform, HP95MM Platform and 95-Platform with angle corners.	1	

Salescode	Extended Description	Qty	
SIGN PLATES			
6750-0004-000-35	Aerial sign plates 12 x 144 (PR). Available on HP78, HP100 and HP100 platform only. Does not include lettering. Color: FLNA 4145 E-ONE BLACK.	1	
6750-0020-000-39	Sign plate for rear of aerial turntable handrails. Single piece painted smooth aluminum plate. Does not include hinges or lettering. Color: Job Color.	1	Manual added by JSTRAWDER on 25-FEB-19
AERIAL TESTING			
6900-0000	Aerial flow test - 3rd party.	1	
6900-0007	Aerial 2016 NFPA Certification.	1	
GROUND LADDERS			
7800-0010	Alco-Lite PRL-16' roof ladder.	2	
7800-0016	Alco-Lite PEL-24' 2-section extension ladder.	1	
7800-0021	Alco-Lite PEL-28' extension ladder.	1	
7800-0024	Alco-Lite PEL-35' extension ladder.	2	
7800-0038	Alco-Lite PRL-20' roof ladder.	1	
7800-0078	Alco-Lite FL-10, 10' folding ladder without shoes and handles.	1	Manual added by BEMASON on 17-AUG-21
MISC LOOSE EQUIPMENT			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1	
7900-0016	Ferno Washington Model 71Stokes	1	
7900-0055	Ferno Millenia 18" wide Backboard	1	
7900-0291	FireCom model UHW505 under helmet wireless radio transmit headset.	2	
7900-0295	FireCom model UHW503 under helmet wireless intercom only headset.	3	Manual qty change by DTALLMAN on 14-NOV-19
7900-0364	Air Hose (1) one low pressure hose 3/8 x 25ft. Includes: 1/4" MNPT couplings with Male National Pipe Thread Ends. Locate: Ship loose.	2	Manual added by JSTRAWDER on 27-SEP-19
EXTERIOR PAINT			
8100-0064	Cab paint break - standard with dip to grille. Break is 31.5" inches below the drip rail on Typhoon, legacy Cyclone and 100" wide Cyclone cabs w/o 4" front raised roof.	1	
8100-0070	Paint valve ends job color.	1	
8100-0084	All applicable pump/pre-connect application modules are to have a job color finish. Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color.	1	

Salescode	Extended Description	Qty	
EXTERIOR PAINT			
8100-0087	Paint Sample Spray Out - Dealer is responsible for returning written approval prior to order release. Two-tone cab color.	1	
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1	
8100-0176-000-17	Paint E-ONE chassis cab - Sikkens paint (non-metallic color). Color: FLNA 3225 E-ONE RED.	1	
8100-0177-000-7W	Paint cab Sikkens two-tone (non-metallic color). Upper area of cab to be painted As Specified.	1	
8100-0183-000-17	Paint Body - Large - For Aerials, T/A Tankers/Wetsides, Rear Mounts and Rescues. Sikkens paint (non-metallic color). Color: FLNA 3225 E-ONE RED.	1	
8100-0354	Paint lift cylinders, extension cylinders and upper turntable steelwork primary job color (does not apply to TT deck).	1	
8100-0372	Paint cab two-tone with approved metallic flake paint color. This is an upcharge and requires applicable cab paint salescode added separately.	1	Manual added by JSCIANNI on 24-SEP-19
INTERIOR PAINT			
8150-0011	The interior of the cab to be painted Zolatone gray.	1	
LETTERING			
8200-0116	Shade and/or outline (EA) for letters as specified by the customer.	200	
8200-0117	Sign Gold Letter (Each) upto 6" tall. The exact size and location of the letters as specified by the customer.	150	
8200-0118	Sign Gold Letter (Each) upto 12" tall. The exact size, color and location of the letters as specified by the customer.	50	
STRIPING			
8200-0016	White reflective tape on (4) outriggers.	1	
8300-0101	Black rubrail scotchlite insert.	1	
8300-0273-000-J7	Chevron "A" style 6" Reflexite V98 striping on front bumper. Colors to be Red/Fluorescent Yellow Green.	1	
8300-0274-000-J7	Chevron "A" style 6" Reflexite V98 striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Red/Fluorescent Yellow Green.	1	
8300-0331	Single NFPA Scotchlite Stripe - up to 6" wide with hockey style, Z or S style or other customer specific design style. Stripe to be installed on cab and the body. Size, color and location as specified by the customer.	1	
8300-0334	Additional NFPA Scotchlite Stripe - upto 3" wide on cab and the body. Design, size, color and location as specified by the customer.	2	

Salescode	Extended Description	Qty	
STRIPING			
8300-0335	A 1/4 in tape pin stripe above and below the scotchlite stripe(s). Color as specified by the customer.	1	
8300-0340	Paint break Sign Gold cab stripe with outline - 3/4" wide total, gold with customer specified outline color. To be located above existing paint break.	1	
8300-0381	Yellow perimeter marking to indicate designated standing / walking areas above 48" high in compliance with 2016 NFPA 1901 consisting of individual Reflexite diamonds approximately 1" wide. Steps, ladders and areas with a railing or structure at least 12" high are excluded from this requirement.	1	
GRAPHICS			
8400-0010-1V4	Install customer logo from an existing E-ONE design (EA). Location: reference graphics layout drawing	6	
8400-0033	Logo E-ONE (PR) on aerial lift cylinder. Logo to be sign gold material approx 14" long located midway along outward surface of cylinder.	1	
8400-0060	Graphics drawing showing striping, lettering and logos. Requires E-ONE installed graphics.	1	
8400-0067	E-ONE logo with grey backing on M6 series vertical tail light housing (PR).	1	
WARRANTY / STANDARD & EXTENDED			
9100-0000	Standard 1 Year Warranty.	1	
9100-0003	Lifetime Frame Structural Warranty.	1	
9100-0004	10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty.	1	
9100-0005	10 Year Stainless Steel Plumbing Warranty - Statement of Warranty.	1	
9100-0007	20 Year Aerial Device Structural Warranty - Integrity Limited Warranty.	1	
9100-0019	10 Year Limited Paint and Perforation Warranty - For Sikkens Paint.	1	
9100-0102	Meritor 5 year unlimited miles, parts and labor rear drive single or rear drive tandem axle warranty.	1	
9100-0104	Dana 5 year unlimited miles, parts and labor front axle warranty.	1	
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS			
9300-0000	Vehicle familiarization aerial (Domestic). 3 days. Use 9300-0315 for additional days.	1	
9300-0009	Manuals, Operator and Service in digital format.	1	
9300-0012	Pump panel approval drawings. Will be provided on purchased units prior to construction.	1	
9300-0016	Approval Drawings-Standard.	1	

Salescode	Extended Description	Qty	
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS			
9300-0031	Dash/Console panel layout approval drawings. Will be provided on purchased units prior to construction.	1	
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1	
Price Adjustment			
Dealer Supplied Equipment			