

September 29th, 2021

City of Pembroke Pines
Public Services Department
Vactor quotation per Sourcewell contract
Attn: Mr. Steven Buckland

The following quote is based on the most current Sourcewell contract. Sourcewell contract #122017-FSC
City of Pembroke Pines Sourcwell Contract Member# 115183

NJPA price for a new 2021 Vactor model 2100 single engine, PD, 15 cubic yard combination sewer cleaning body with a 2022 Freightliner model 114SD tandem axle truck cab/chassis (Spec attached)

\$419,296.81

MEMPHIS

2995 Sandbrook St. Memphis, TN 38116 **P:** 901.630.5658 **F:** 901.630.5659

DEERFIELD BEACH

1907 SW 43rd Terrace Suites G & H Deerfield Bch, FL 33442 **P:** 954.518.9923 **F:** 954.518.9926

ATLANTA

4410 Wendell Dr SW Atlanta, GA 30336 **P:** 404.693.9700 **F:** 404.693.9690

CORPORATE

2525 Clarcona Rd. Apopka, FL 32703 **P:** 407.798.0004 **F:** 407.798.0013 Vactor warranty is standard 1 year parts and labor, excluding common wear items. The water pump is covered for 2 years parts and labor. The PD vacuum blower has a 1 year warranty. The water tanks carry a 10 year warranty and the debris tank carries a 5 year warranty.

Vactor warranty covers the PTO, hydraulic pumps and system, pneumatic system, water system, electrical system, switches, valves, transfer case, shafts, cylinders, etc.

PRODUCT DESCRIPTION

· 2100i with Roots 824-16" Hg. Blower, 15 Yard Debris body, 1500 Gallons of Fresh Water

STANDARD FEATURES

- · 48" x 22" x 24" Curb Side Aluminum Toolbox
- · Aluminum Fenders
- · Mud Flaps
- · Electric/Hydraulic Four Way Boom
- · Color Coded Sealed Electrical System
- · Remote Pendant Control w/35' Cord



- · Intuitouch Electronic Package
- · Double Acting Dump Hoist Cylinder
- · Handgun Assembly
- · 3" Y-Strainer at Water Pump Inlet
- · Ex-Ten Steel Cylindrical Debris Tank
- · Flexible Hose Guide
- · 30 Deg. Sand Nozzle w/Carbide Inserts
- · 30 Deg. Sanitary Nozzle w/Carbide Inserts
- · 15 Deg. Penetrator Nozzle w/Carbide Inserts
- · Nozzle Storage Rack
- · Vacuum Tube Storage: Curbside (2) Pipe, Rear Door (2) Pipe
- · 1" Nozzle
- · 10' Leader Hose
- · Flat Rear Door w/Hydraulic Locks and Door Power-up/Down, Open/Close Feature
- · Dual 10" Stainless Steel Float Shut Off System/Rear Mounted
- · Debris Body Vacuum Relief System
- · Debris Deflector Plate
- · 60" Dump Height
- · Water Sight Gauge DS/PS
- · Liquid Float Level Indicator
- · Boom Transport Post Storage
- 3" Y-Strainer @ Water Pump w/3" Drain Valve
- · Performance Package: (Hyd Variable Flow, Dual PTO's. Dual Hyd. Pumps)
- · 1" Water Relief Valve for Vactor Water Pump
- · Stainless Steel Microstrainer
- · Blower Air Shift Controls
- · Hydraulic Cooling Package
- · Midship Handgun Coupling
- · Side Mounted Water Pump
- · Hose Wind Guide (Dual Roller)
- · Hose Reel Manual Hyd. Extend/Retract
- · Hose Reel Chain Cover (Full)
- · Tachometer/Chassis Engine W/Hourmeter
- · Circuit Breakers
- · LED Lights. Clearance, Back-Up, Stop, Tail & Turn
- · Tow Hooks, Front and Rear
- · Electronic Back-Up Alarm
- · Hydraulic Tank Shutoff Valves
- · 8" Vacuum Pipe Package
- · Emergency Flare Kit
- · Fire Extinguisher 5 Lbs.
- · Fixed Rear Door Pipe Rack, 8" Pipe
- · Low Water Alarm with Water Pump Flow Indicator
- · Front Joystick Boom Control
- · Rodder System Accumulator- Jack Hammer on/off control w/ manual valve
- · Digital Hose Footage Counter
- · Water Pump Hour Meter

MEMPHIS

2995 Sandbrook St. Memphis, TN 38116 **P:** 901.630.5658 **F:** 901.630.5659

DEERFIELD BEACH

1907 SW 43rd Terrace Suites G & H Deerfield Bch, FL 33442 **P:** 954.518.9923 **F:** 954.518.9926

ATLANTA

4410 Wendell Dr SW Atlanta, GA 30336 **P:** 404.693.9700 **F:** 404.693.9690

CORPORATE

2525 Clarcona Rd. Apopka, FL 32703 **P:** 407.798.0004 **F:** 407.798.0013



- · PTO Hour Meter
- · Hydraulic Oil Temp Alarm
- · Digital Water Pressure Gauge
- · Chassis Modifications

ADDITIONAL FEATURES

- · Roots 824-16" Hg. Blower
- · 180 Degree Rotation, 10 Ft. Hydraulic Telescoping Boom, Front Loading 8" Suction Hose
- · Telescopic Boom Elbow, Nickel Plated
- · 80 GPM Variable Flow Water System
- · 2500 PSI Water Pressure
- · 1" x 600' Piranha Sewer Hose, 2500 PSI
- · Hydraulic Extending/Rotating 15" Hose Reel (1" x 800') Capacity
- · Module Paint, Dupont Imron Elite Sanded Primer Base
- · Debris Body Flush Out System
- · 6" Knife Valve w/Cam-Loc, Rear Door, 6:00 Position
- · Standpipe and Screen for 6:00 Port
- · 304SS Centrifugal Separators, Dustboxes, Plenum and Crossover Tubes
- · Folding Pipe Rack, Curbside, 8" Pipe
- · Folding Pipe Rack, Streetside, 8" Pipe
- · Rear Door Splash Shield
- · Lube Manifold
- · Plastic Lube Chart
- · Wireless Controls, including hose reel controls
- · Rotatable Boom Inlet Hose, Telescoping Boom
- · Anti Splash Valve
- · Hydro Excavation Kit Includes Lances, Nozzles, Storage Tray, and Vacuum Tubes
- · Automatic Hose Level Wind Guide, Indexing
- · High Pressured Hose Reel
- · Rodder Pump Drain Valves
- · Rear Directional Control, LED Arrowstick
- · Waterproof, Rechargeable, Wireless, Handheld, LED Spot Light w/12V Charger and Plug
- · 14 Lighting Package, 14 Federal Signal Strobe Lights, LED
- · Worklights (2), LED, Telescoping Boom
- · Worklight, LED, Curb Side
- · Toolbox, Front Bumper Mounted, 16 x 12 x 18 w/(2) LED Side Markers
- · Toolbox, Behind Cab
- · Toolbox, Driver Side Chassis Frame, 24w x 24h x 24d
- · Camera System, Front, Rear and Both Sides
- · Safety Cone Storage Rack Post Style
- · Digital Water Level Indicator
- · Digital Debris Body Level Indicator
- · (2) 8" x 5' Aluminum Vacuum Tube (30' total)
- · (2) 8" Quick Clamp Assembly (6 clamps total)
- · (1) 8" Adjustable Air Adapter

MEMPHIS

2995 Sandbrook St. Memphis, TN 38116 **P:** 901.630.5658 **F:** 901.630.5659

DEERFIELD BEACH

1907 SW 43rd Terrace Suites G & H Deerfield Bch, FL 33442 **P:** 954.518.9923 **F:** 954.518.9926

ATLANTA

4410 Wendell Dr SW Atlanta, GA 30336 **P:** 404.693.9700 **F:** 404.693.9690

CORPORATE

2525 Clarcona Rd. Apopka, FL 32703 **P:** 407.798.0004 **F:** 407.798.0013



- · Vactor Supplied Chassis, Tandem Axle, 2022 Freightliner 114SD SBA 6x4, 370 HP, Auto, 66,000 GVWR, GHG
- · Vactor Standard Manual and USB Version 1

Please contact me with any questions.

Sincerely,

Paul A. Hart

Paul A. Hart South Florida Sales Manager Environmental Products Group 561-719-1395 Cell phart@myepg.com

MEMPHIS

2995 Sandbrook St. Memphis, TN 38116 **P:** 901.630.5658 **F:** 901.630.5659

DEERFIELD BEACH

1907 SW 43rd Terrace Suites G & H Deerfield Bch, FL 33442 **P:** 954.518.9923 **F:** 954.518.9926

ATLANTA

4410 Wendell Dr SW Atlanta, GA 30336 **P:** 404.693.9700 **F:** 404.693.9690

CORPORATE

2525 Clarcona Rd. Apopka, FL 32703 **P:** 407.798.0004 **F:** 407.798.0013



Phone: 1 404-693-9700

A proposal for VACTOR MANUFACTURING ENVIRONMENTAL PRODUCTS PAFT370A 2022

2100i CUMMINS L9 TANDEM AXLE

Oct 30, 2020

Freightliner 114SD



Components shown may not reflect all spec'd options and are not to scale



Prepared for: 2022 PAFT370A STOCK VACTOR MANUFACTURING EPOF PAFT370A 2022 2525 CLARCONA ROAD APOPKA, FL 32703 Phone: 1 404-693-9700

SPECIFICATION PROPOSAL

	Data Code	Description	Weight Front	Weight Rear	
Price Le	evel				
	PRL-20D	SD PRL-20D (EFF:04/30/19)			
Data Ve	rsion				
	DRL-040	SPECPRO21 DATA RELEASE VER 040			
Vehicle	Configuratio	n			
	001-177	114SD CONVENTIONAL CHASSIS	7,934	6,476	
	004-222	2022 MODEL YEAR SPECIFIED			
	002-004	SET BACK AXLE - TRUCK	480	-480	
	019-002	STRAIGHT TRUCK PROVISION			
	003-001	LH PRIMARY STEERING LOCATION			
General	Service				
	AA1-002	TRUCK CONFIGURATION			
	AA6-001	DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)			
	A85-010	UTILITY/REPAIR/MAINTENANCE SERVICE			
	A84-1GM	GOVERNMENT BUSINESS SEGMENT			
	AA4-002	LIQUID BULK COMMODITY			
	AA5-006	TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN TRANSIT, IS SPENT ON NON-PAVED ROADS			
	AB1-008	MAXIMUM 8% EXPECTED GRADE			
	AB5-003	MAINTAINED GRAVEL OR CRUSHED ROCK - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE			
	995-1AE	FREIGHTLINER LEVEL II WARRANTY			
	A66-99D	EXPECTED FRONT AXLE(S) LOAD: 20000.0 lbs			
	A68-99D	EXPECTED REAR DRIVE AXLE(S) LOAD: 46000.0 lbs			
	A63-99D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 66000.0 lbs			
Truck S	ervice				
	AA3-034	SEWER/INDUSTRIAL VACUUM BODY			

	Data Code	Description	Weight Front	Weight Rear	
	A88-99D	EXPECTED TRUCK BODY LENGTH: 0.0 ft			
	AE2-99D	EXPECTED TRUCK BODY WIDTH: 96.0 in			
	A89-99D	BRAKING-EXPECTED CAB TO BODY CLEARANCE: 3.0 in			
	AF3-1DN	VACTOR			
Engine					
	101-3BU	CUM L9 370 HP @ 2100 RPM; 2100 GOV RPM, 1250 LB-FT @ 1200 RPM	-850	-70	
Electro	nic Paramete	ers			
	79A-070	70 MPH ROAD SPEED LIMIT			
	79B-000	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT			
	79K-005	PTO MODE ENGINE RPM LIMIT - 900 RPM			
	79M-001	PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED			
	79P-002	PTO RPM WITH CRUISE SET SWITCH - 700 RPM			
	79Q-003	PTO RPM WITH CRUISE RESUME SWITCH - 800 RPM			
	79S-001	PTO MODE CANCEL VEHICLE SPEED - 5 MPH			
	79U-007	PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND			
	80G-002	PTO MINIMUM RPM - 700			
	80J-002	REGEN INHIBIT SPEED THRESHOLD - 5 MPH			
Engine	Equipment				
	99C-021	2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG21 CONFIGURATION			
	99D-009	2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LEFT SIDE OF HOOD)			
	13E-001	STANDARD OIL PAN			
	105-001	ENGINE MOUNTED OIL CHECK AND FILL			
	014-1B5	SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED			
	124-1D7	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE			
	292-235	(2) DTNA GENUINE, FLOODED STARTING, MIN 2000CCA, 370RC, THREADED STUD BATTERIES	-50	-10	
	290-017	BATTERY BOX FRAME MOUNTED			
	281-001	STANDARD BATTERY JUMPERS			

APOPKA, FL 32703 Phone: 1 404-693-9700

Data Code	Description	Weight Front	Weight Rear	
282-001	SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB			
291-017	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN			
289-001	NON-POLISHED BATTERY BOX COVER			
107-032	CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE			
152-040	ELECTRONIC ENGINE INTEGRAL WARNING AND DERATE PROTECTION SYSTEM			
128-076	CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE GEOMETRY TURBO ON/OFF	20		
016-1C2	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE	30	25	
28F-002	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH			
239-200	INTEGRATED STACK AND B-PILLAR PIPE WITH MINIMUM STACK PROTRUSION ABOVE CAB			
237-1CR	RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP			
23U-002	13 GALLON DIESEL EXHAUST FLUID TANK			
30N-003	100 PERCENT DIESEL EXHAUST FLUID FILL			
23Y-001	STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING			
43X-002	LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION			
43Y-001	STANDARD DIESEL EXHAUST FLUID TANK CAP			
242-001	STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD			
273-048	HORTON 2-SPEED DRIVEMASTER ADVANTAGE POLAREXTREME FAN DRIVE			
276-002	AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED			
110-003	CUMMINS SPIN ON FUEL FILTER			
118-008	COMBINATION FULL FLOW/BYPASS OIL FILTER			
266-017	1300 SQUARE INCH ALUMINUM RADIATOR	-20		
103-036	ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE- CHARGED SCA HEAVY DUTY COOLANT			
171-007	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT			

Data Code	Description	Weight Front	Weight Rear	
172-001	CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES			
270-016	RADIATOR DRAIN VALVE			
138-011	PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4		
140-022	CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR			
132-004	ELECTRIC GRID AIR INTAKE WARMER			
155-055	DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH			
Transmission				
342-582	ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION			
Transmission Equip	pment			
343-323	ALLISON VOCATIONAL PACKAGE 172 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODEL RDS			
84B-012	ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES			
84C-023	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
84D-023	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
84E-000	PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			
84F-000	SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			
84G-000	PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			
84H-000	SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			
84N-200	FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED			
84U-000	DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES			



APOPKA, FL 32703 Phone: 1 404-693-9700

Data C	Code [Description	Weight Front	
84M-0	01 F	PUMP MODE INPUT ENABLED 3RD/4TH LOCKUP WIRED ON TCM INPUT AJ/BQ - ALLISON 5TH GEN TRANSMISSIONS		
353-02		/EHICLE INTERFACE WIRING CONNECTOR WITHOUT BLUNT CUTS, AT BACK OF CAB		
34C-00		ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR FIREWALL MOUNTED		
362-1		2) CUSTOMER INSTALLED MUNCIE CS10 SERIES PTO'S		
363-01		PTO MOUNTING, LH AND RH SIDES OF MAIN FRANSMISSION		
341-01	٦	MAGNETIC PLUGS, ENGINE DRAIN, FRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
345-00		PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED		
97G-00	04 7	FRANSMISSION PROGNOSTICS - ENABLED 2013		
370-01		NATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK	-15	
346-00		FRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
35T-00		SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		
Front Axle an	d Equipn	nent		
400-1		MFS-20-133A 20,000# FL1 71.0 INCH KPI/3.74 NCH DROP SINGLE FRONT AXLE	260	
402-03	E	MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	10	
403-00)2 1	NON-ASBESTOS FRONT BRAKE LINING		
419-02	23 (CONMET CAST IRON FRONT BRAKE DRUMS		
409-00)6 F	FRONT OIL SEALS		
408-00		/ENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
416-02	22 8	STANDARD SPINDLE NUTS FOR ALL AXLES		
405-00		MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
406-00)1 5	STANDARD KING PIN BUSHINGS		
536-05		FRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR	130	
539-00)3 F	POWER STEERING PUMP		
534-00)3 4	QUART POWER STEERING RESERVOIR		
533-00)1 (DIL/AIR POWER STEERING COOLER		

	Data Code	Description	Weight Front	Weight Rear	
	40T-001	MINERAL SAE 80/90 FRONT AXLE LUBE			
Front S	Suspension				
	620-006	20,000# FLAT LEAF FRONT SUSPENSION	310		
	619-004	GRAPHITE BRONZE BUSHINGS WITH SEALS - FRONT SUSPENSION			
	62G-998	NO FRONT SUSPENSION OPTIONS			
	62H-014	LEFT AND RIGHT FRONT SUSPENSION REAR SHACKLE PINS WITH ZERK FITTINGS OUTBOARD			
	410-001	FRONT SHOCK ABSORBERS			
Rear A	xle and Equ	ipment			
	420-111	RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE		450	
	421-563	5.63 REAR AXLE RATIO			
	424-001	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING			
	385-005	JACKSHAFT, TEMPORARY DRIVELINE FOR CUSTOMER FURNISHED EQUIPMENT, TEMPORARILY INSTALLED FOR SHIPPING TO CUSTOMER/TEM	40	40	
	,	VACTOR REF 504400JA REF VIN MD9033			
	386-011	SPL170 XL DANA SPICER MAIN DRIVELINE WITH HALF ROUND YOKES	45	45	
	1	MOUNT CARRIER BEARING ON 562 CROSSMEMBER RE	EF S/N MD9033		
	388-012	SPL170 XL DANA SPICER INTERAXLE DRIVELINE WITH HALF ROUND YOKES		10	
	878-019	(1) INTERAXLE LOCK VALVE FOR TANDEM OR TRIDEM DRIVE AXLES			
	87A-001	BLINKING LAMP WITH EACH INTERAXLE LOCK SWITCH, INTERAXLE UNLOCK DEFAULT WITH IGNITION OFF			
	423-020	MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES			
	433-002	NON-ASBESTOS REAR BRAKE LINING			
	434-003	STANDARD BRAKE CHAMBER LOCATION			
	451-023	CONMET CAST IRON REAR BRAKE DRUMS		20	
	440-006	REAR OIL SEALS			
	426-101	WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS			
	428-003	HALDEX AUTOMATIC REAR SLACK ADJUSTERS			
	41T-001	MINERAL SAE 80/90 REAR AXLE LUBE			

APOPKA, FL 32703 Phone: 1 404-693-9700

Data Code	Description	Weight Front	Weight Rear	
42T-001	STANDARD REAR AXLE BREATHER(S)			
Rear Suspension				
622-1CJ	HENDRICKSON RT463 @46,000# REAR SUSPENSION		750	
621-015	HENDRICKSON RT/RTE - 6.00" SADDLE			
431-001	STANDARD AXLE SEATS IN AXLE CLAMP GROUP			
624-009	54 INCH AXLE SPACING		10	
628-005	STEEL BEAMS AND BRONZE CENTER BUSHINGS WITH BAR PIN ADJUSTABLE END CONNECTIONS			
623-005	FORE/AFT CONTROL RODS			
Brake System				
490-100	WABCO 4S/4M ABS			
871-001	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES			
904-001	FIBER BRAID PARKING BRAKE HOSE			
412-001	STANDARD BRAKE SYSTEM VALVES			
46D-002	STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM			
413-1AA	STANDARD U.S. FRONT BRAKE VALVE WITH ABS VALVES IN RAILS WITH RH HEAT SHIELDING			
432-003	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE			
480-009	BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20		
483-003	BENDIX OIL COALESCING FILTER FOR AIR DRYER			
479-034	AIR DRYER MOUNTED INBOARD ON LH RAIL, LOCATE AT 4400			
460-093	STEEL AIR BRAKE RESERVOIRS; CUSTOMER ACCEPTS TANKS MOUNTED PERPENDICULAR TO RAIL	10	10	
	MOUNT PERPENDICULAR REAR OF AFTERTREATME AFTERFRAME	NT AT 3100. MOUI	NT REMAING TANK	(S IN
477-001	PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS			
485-045	METALLIC AIR MANIFOLD MOUNTED TO BACK OF CAB CROSSMEMBER WITH SIX 1/4 INCH FITTINGS AND 70 PSI PROTECTION VALVE	5		

Trailer Connections

335-004 UPGRADED CHASSIS MULTIPLEXING UNIT



Data Code	Description	Weight Front	Weight Rear	
32A-002	UPGRADED BULKHEAD MULTIPLEXING UNIT			
Wheelbase & Frame				
545-662	6625MM (261 INCH) WHEELBASE			
546-102	7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI	770	140	
547-001	1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT	270	450	
552-038	1800MM (71 INCH) REAR FRAME OVERHANG			
55W-007	FRAME OVERHANG RANGE: 71 INCH TO 80 INCH	-30	130	
549-002	24 INCH INTEGRAL FRONT FRAME EXTENSION	140	-20	
AC8-99D	CALC'D BACK OF CAB TO REAR SUSP C/L (CA): 195.28 in			
AE8-99D	CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA): 192.28 in			
AE4-99D	CALC'D FRAME LENGTH - OVERALL: 401.33			
FSS-0LH	CALCULATED FRAME SPACE LH SIDE: 98.0 in			
FSS-0RH	CALCULATED FRAME SPACE RH SIDE: 223.23 in			
AM6-99D	CALC'D SPACE AVAILABLE FOR DECKPLATE : 195.45 in			
553-001	SQUARE END OF FRAME			
550-001	FRONT CLOSING CROSSMEMBER			
559-001	STANDARD WEIGHT ENGINE CROSSMEMBER			
562-057	STANDARD MIDSHIP #1 CROSSMEMBERS LOCATED AT H:3200 AND H:4800			
569-005	INCREASED CROSSMEMBER SPACING REQ'D BY ENGINEERING			
572-067	STANDARD REARMOST CROSSMEMBER MOUNTED 960MM AFT OF REAR SUSPENSION CROSSMEMBER			
565-001	STANDARD SUSPENSION CROSSMEMBER			
Chassis Equipment				
556-997	OMIT FRONT BUMPER, CUSTOMER INSTALLED SPECIAL BUMPER, DOES NOT COMPLY WITH FMCSR 393.203	-100		
551-017	GRADE 8 THREADED HEX HEADED FRAME FASTENERS INSTALLED WITH BOLT HEADS ON OUTSIDE OF FRAME			
606-155	DRILLING PREP FOR VACTOR PER DRAWING 504400JA, REVISION 0 10/14/2015			

	Data Code	Description	Weight Front	Weight Rear	
	605-1AB	D15-16004-000 CENTER PUNCH TO MARK CENTERLINE OF REAR SUSPENSION ON FRAME WEB			
Fuel T	anks				
	204-155	90 GALLON/340 LITER ALUMINUM FUEL TANK - LH	15		
	218-006	25 INCH DIAMETER FUEL TANK(S)			
	215-005	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS			
	212-007	FUEL TANK(S) FORWARD			
	664-001	PLAIN STEP FINISH			
	205-001	FUEL TANK CAP(S)			
	122-1H3	DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR	10		
	216-020	EQUIFLO INBOARD FUEL SYSTEM			
	20E-004	AUXILIARY FUEL SUPPLY AND RETURN PORTS LOCATED ON LH FUEL TANK			
	202-016	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE			
	221-012	FUEL COOLER MOUNTED INSIDE RIGHT HAND IN RAIL AT 2950			
Tires					
	093-0TB	MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL FRONT TIRES	196		
	094-1UX	MICHELIN X MULTI D 11R22.5 14 PLY RADIAL REAR TIRES		192	
Hubs					
	418-060	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS			
	450-060	CONMET PRESET PLUS PREMIUM IRON REAR HUBS			
Wheel	S				
	502-1H5	ALCOA LVL ONE 82462X 22.5X12.25 10-HUB PILOT 4.68 INSET 10-HAND ALUMINUM DISC FRONT WHEELS	-8		
	505-693	ALCOA LVL ONE 88267X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS		-200	
	524-001	POLISHED FRONT WHEELS; OUTSIDE ONLY			
	525-001	POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY			



APOPKA, FL 32703 Phone: 1 404-693-9700

Data	Code	Description	Weight Front	Weight Rear	
52M-	004	FOREMATCH TIRE/WHEEL RUNOUT CHECK/MARK AND STATIC BALANCING. ALL TIRES AND WHEELS			
Cab Exterior	•				
829-1	A2	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB			
650-0	800	AIR CAB MOUNTING			
648-0	002	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE			
667-0	004	FRONT FENDERS SET-BACK AXLE			
754-0)17	BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS	10		
678-0)18	LH AND RH EXTERIOR GRAB HANDLES WITH SINGLE RUBBER INSERT			
645-0	002	BRIGHT FINISH RADIATOR SHELL/HOOD BEZEL			
646-0)42	STATIONARY BLACK GRILLE WITH BRIGHT ACCENTS			
65X-0	003	CHROME HOOD MOUNTED AIR INTAKE GRILLE			
644-0	004	FIBERGLASS HOOD			
690-0	002	TUNNEL/FIREWALL LINER			
727-1	AF	SINGLE 14 INCH ROUND HADLEY AIR HORN UNDER LH DECK			
726-0	001	SINGLE ELECTRIC HORN			
728-0	001	SINGLE HORN SHIELD			
657-0	001	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME			
78G-(004	KEY QUANTITY OF 4			
312-0	067	HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS			
302-0)47	LED AERODYNAMIC MARKER LIGHTS			
311-0)12	DAYTIME RUNNING LIGHTS - LOW BEAM ONLY			
294-0	001	INTEGRAL STOP/TAIL/BACKUP LIGHTS			
300-0)15	STANDARD FRONT TURN SIGNAL LAMPS			
744-1	IBC	DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE			
797-0	001	DOOR MOUNTED MIRRORS			
796-0	001	102 INCH EQUIPMENT WIDTH			
743-2	204	LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS			
74A-0	001	RH DOWN VIEW MIRROR			

APOPKA, FL 32703 Phone: 1 404-693-9700

Data Co	ode Descr	iption	Weigh Fron	_	
729-001	STAN	DARD SIDE/REAR REFLECTORS			
768-043	63X14	INCH TINTED REAR WINDOW			
661-004		D DOOR GLASS LH AND RH WITH TINTE ATING WING WINDOWS	D		
654-027		ND LH ELECTRIC POWERED WINDOWS, ENGER SWITCHES ON DOOR(S)	•	4	
663-013	1-PIE	CE SOLAR GREEN GLASS WINDSHELD			
659-006	RESE	R (2 GAL) WINDSHIELD WASHER RVOIR, CAB MOUNTED, WITH FLUID LINDICATOR			
Cab Interior					
707-1Al	(OPAL	GRAY VINYL INTERIOR			
706-026	VINYL	ED PLASTIC DOOR PANEL WITHOUT INSERT WITH ALUMINUM KICKPLATE R DOOR			
708-026	VINYL	ED PLASTIC DOOR PANEL WITHOUT INSERT WITH ALUMINUM KICKPLATE R DOOR			
772-006	BLAC	K MATS WITH SINGLE INSULATION			
785-001	DASH	MOUNTED ASH TRAYS AND LIGHTER			
691-008		/ARD ROOF MOUNTED CONSOLE WITH R STORAGE COMPARTMENTS WITHOUT NG			
694-010	IN DA	SH STORAGE BIN			
742-007	(2) CL	IP HOLDERS LH AND RH DASH			
680-006	GRAY	/CHARCOAL FLAT DASH			
860-004	SMAR	T SWITCH EXPANSION MODULE			
700-002	HEAT	ER, DEFROSTER AND AIR CONDITIONER	2		
701-008		DARD HVAC DUCTING WITH SNOW D FOR FRESH AIR INTAKE			
703-005	MAIN SWIT	HVAC CONTROLS WITH RECIRCULATION CH	N		
689-804	AUXIL	KIT FOR CUSTOMER INSTALLED IARY HEATER, PLUMBING FROM ENGINI IIL UNDER CAB WITH SHUTOFF VALVES	= 29	5	
170-019		DARD HEATER PLUMBING WITH BALL OFF VALVES			
724-001	AUXIL	IARY HEATER PLUMBING			
130-041		O HEAVY DUTY A/C REFRIGERANT PRESSOR			
702-002	BINAF	RY CONTROL, R-134A			
739-034	PREM	IUM INSULATION			

APOPKA, FL 32703 Phone: 1 404-693-9700

Data C	ode D	Description	Weight Front	Weight Rear	
285-01	3 S	OLID-STATE CIRCUIT PROTECTION AND USES			
280-00	7 1	2V NEGATIVE GROUND ELECTRICAL SYSTEM			
324-01	-	OME LIGHT WITH 3-WAY SWITCH ACTIVATED Y LH AND RH DOORS			
655-00)5 L	H AND RH ELECTRIC DOOR LOCKS			
284-02	23 (*	1) 12 VOLT POWER SUPPLY IN DASH			
756-1J	S	ASIC HIGH BACK AIR SUSPENSION DRIVER EAT WITH MECHANICAL LUMBAR AND NTEGRATED CUSHION EXTENSION	30		
760-1J	F	ASIC HIGH BACK AIR SUSPENSION ASSENGER SEAT WITH MECHANICAL LUMBAR ND INTEGRATED CUSHION EXTENSION	25	10	
759-00		UAL DRIVER AND PASSENGER SEAT RMRESTS	8		
711-00)4 L	H AND RH INTEGRAL DOOR PANEL ARMRESTS			
758-02	.2 B	LACK MORDURA CLOTH DRIVER SEAT COVER			
761-02		LACK MORDURA CLOTH PASSENGER SEAT COVER			
763-10)2 F	IIGH VISIBILITY ORANGE SEAT BELTS			
532-00		DJUSTABLE TILT AND TELESCOPING TEERING COLUMN	10		
540-01	5 4	-SPOKE 18 INCH (450MM) STEERING WHEEL			
765-00	_	RIVER AND PASSENGER INTERIOR SUN ISORS			
Instruments 8	& Control	s			
732-00)4 G	RAY DRIVER INSTRUMENT PANEL			
734-00)4 G	GRAY CENTER INSTRUMENT PANEL			
87L-00		NGINE REMOTE INTERFACE WITHOUT NTERLOCKS			
870-00)1 B	LACK GAUGE BEZELS			
486-00		OW AIR PRESSURE INDICATOR LIGHT AND UDIBLE ALARM			
840-00		INCH PRIMARY AND SECONDARY AIR RESSURE GAUGES			
198-00		ASH MOUNTED AIR RESTRICTION INDICATOR VITH GRADUATIONS			
721-00)1 9	7 DB BACKUP ALARM		3	
149-01		LECTRONIC CRUISE CONTROL WITH WITCHES IN LH SWITCH PANEL			
156-00	11	EY OPERATED IGNITION SWITCH AND NTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY			

Data Code	Description	Weight Front	Weight Rear	
811-042	ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED			
160-039	(1) HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH AND (1) SAE J1939 DIAGNOSTIC INTERFACE CONNECTOR LOCATED CENTER OF DASH			
844-001	2 INCH ELECTRIC FUEL GAUGE			
148-071	ENGINE REMOTE INTERFACE WITH INCREMENT/DECREMENT			
163-004	ENGINE REMOTE INTERFACE CONNECTOR IN ENGINE COMPARTMENT			
33U-002	VACTOR INTERLOCK PREP			
856-001	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE			
864-005	TRANSMISSION OIL TEMPERATURE INDICATOR LIGHT			
830-017	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY			
372-051	CUSTOMER FURNISHED AND INSTALLED PTO CONTROLS			
852-002	ELECTRIC ENGINE OIL PRESSURE GAUGE			
746-116	AM/FM/WB WORLD TUNER RADIO WITH SIRIUS XM, CD PLAYER, BLUETOOTH, IPOD INTERFACE AND USB AND AUXILIARY INPUTS, J1939	10		
747-001	DASH MOUNTED RADIO			
750-002	(2) RADIO SPEAKERS IN CAB			
753-001	AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF			
78C-003	INTEROPERABLE SDAR ANTENNA			
810-027	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER			
817-001	STANDARD VEHICLE SPEED SENSOR			
812-001	ELECTRONIC 3000 RPM TACHOMETER			
813-998	NO VEHICLE PERFORMANCE MONITOR	-5		
6TS-003	(2) TMC RP 1226 ACCESSORY CONNECTORS: (1) LOCATED BEHIND DASH B PANEL AND (1) LOCATED PASSENGER SIDE OF DASH			
162-002	IGNITION SWITCH CONTROLLED ENGINE STOP			
81Y-001	PRE-TRIP LAMP INSPECTION, ALL OUTPUTS FLASH, WITH SMART SWITCH			
836-015	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY			

APOPKA, FL 32703 Phone: 1 404-693-9700

	Data Code	Description	Weight Front	Weight Rear		
	660-008	SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY				
	304-001	MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH				
	882-009	ONE VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR				
	299-013	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE				
	298-039	INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS				
Design						
	065-000	PAINT: ONE SOLID COLOR				
Color						
	980-5F6	CAB COLOR A: L0006EY WHITE ELITE EY				
	986-020	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT				
_	963-003	STANDARD E COAT/UNDERCOATING				
Certific	ation / Comp	liance				
	996-001	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS				
Second	Secondary Factory Options					
	999-047	JACKSHAFT ASSEMBLIES ARE FOR TEMPORARY USE AND SHOULD BE USED FOR SHIPPING TO CUSTOMER/BODY BUILDER				
Raw Pe	erformance Da	ata				
	AE8-99D	CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA): 192.28 in				
	AM6-99D	CALC'D SPACE AVAILABLE FOR DECKPLATE : 195.45 in				

Weight Summary			
	Weight	Weight	Total
	Front	Rear	Weight
Factory Weight ⁺	9743 lbs	7981 lbs	17724 lbs

TOTAL VEHICLE SUMMARY



APOPKA, FL 32703 Phone: 1 404-693-9700

Total Weight⁺ 9743 lbs 7981 lbs 17724 lbs

Extended Warranty

WAG-010 TOWING: 1 YEAR/UNLIMITED MILES/KM EXTENDED TOWING COVERAGE \$550 CAP FEX APPLIES

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.



Page 16 of 18

Prepared for: 2022 PAFT370A STOCK VACTOR MANUFACTURING EPOF PAFT370A 2022 2525 CLARCONA ROAD APOPKA, FL 32703 Phone: 1 404-693-9700

Prepared for: 2022 PAFT370A STOCK VACTOR MANUFACTURING EPOF PAFT370A 2022 2525 CLARCONA ROAD APOPKA, FL 32703 Phone: 1 404-693-9700





Federal Signal #122017-FSC

Pricing for contract #122017-FSC offers Sourcewell participating agencies the following discounts:

- Elgin 3% Discount from list price
- Vactor 3% Discount from list price
- Additional discounting may be considered for volume purchases or unique situations handled on a caseby-case basis